

## ANUChrome – LEMON Chrome L-24

ANUChrome Lemon Chrome L-24 is a monoclinic Lead Chromate material, also known as Pre-Darkened Lemon Chrome. This pigment is highly stabilized and is of very good light fastness and exterior durability.

Therefore, it is suitable for high grade automotive coatings meant for refinishing purposes. It possesses good resistance to acidic environment.

### TECHNICAL DATA

Colour Index No.	77603
Colour Index Pigment No.	Y-34
Oil Absorption	16-21
Specific Gravity	4.9-6.0
Bulk Density g/cc	0.76
<b>BLEEDING IN (1-Poor 5-Excellent)</b>	
Water	5
5% Caustic Soda	3
5% Hydrochloric Acid	3
Linseed Oil	5
Ethanol	5
Ethyl Acetate	5
Xylene	5
n-Butanol	5
Methyl Ethyl Ketone	5
Mineral Turpentine	5
Cellosolve	5
Diocetyl Phthalate	5
<b>RESISTANCE TO HEAT</b>	
120°C / 30 min.	SB
150°C / 20 min.	SB
180°C / 10 min.	USB
210°C / 10 min.	USB
<b>RESISTANCE TO LIGHT</b>	
Full Tone	7
Tint Tone (1:10)	7
<b>RESISTANCE TO</b>	
Acid	G
Alkali	P
<b>APPLICATIONS</b>	
Paints	*
Printing Inks	*
Rubber	
Leather Pastes	*
Linoleum	*
PVC Leather Cloth	*
Paper Coating	*

Chalk / Crayons	
Plastics	*

## LEGEND

COLOUR	BLEEDING	HEAT STABILITY	LIGHTFASTNESS	APPLICATIONS	
Y – YELLOW	SCALE (1-5)	SB : STABLE	SCALE (1-8)	* :RECOMMENDED/ MAYBE USED	<b>E</b> – EXCELLENT
R – RED	5:NO BLEED	USB : UNSTABLE	1 – POOR		<b>VG</b> – VERY GOOD
W – WHITE	1:CONSIDERABLE BLEED		8 – EXCELLENT		<b>G</b> – GOOD
					<b>F</b> – FAIR
					<b>P</b> – POOR