

Goldstab Lead Octoate 24%

Description	Goldstab Lead Octoate is a metal carboxylate or metal salts of carboxylic acids. It is one of the auxiliary driers also called as through drier.	
Typical Properties	Physical form	Clear liquid
	Color	Light yellow or Gardener 3
	Metal content	24 ± 0.2%
	Non-volatile matter	46 ± 5%
	Viscosity	13 ± 5 secs at 30°C
	Specific Gravity	1.08 ± 0.2
Features and benefits	Goldstab Lead Octoate 24% promotes hard, through drying throughout the entire film.	
Applications	Recommended to be used in: Paints, coatings and inks Hardening of Polyurethane and Unsaturated Polyester Resin Lubricants and Grease Rubber Industry	
Guidelines for use	Dosage of 0.5 to 3.0 parts of Goldstab Lead Octoate per 100 parts of resin is recommended. Depending upon various factors such as active functional groups, glass transition temperature and other additives used in formulation the final formulation can be optimized. Extensive performance data of Goldstab Lead Octoate is available upon request.	
Handling Instructions	Goldstab Lead Octoate is a toxic product and proper care should be taken while handling. It is highly recommended to use nose mask and gloves and avoid unnecessary personal contact.	
Shelf life	It is recommended that Goldstab Lead Octoate should be used before 24 months from the date of manufacturing	

Note: The information and data provided herein in is good faith and are based on the current knowledge and experience of Goldstab Organics Pvt. Ltd. As there are many factors that may affect the processing and use of product, we recommend users to carry investigations and tests to determine suitability of the product for particular purpose prior to use.