## **Technical Data Sheet**



## **Goldstab Manganese Octoate 8%**

**Description** Manganese Octoate 8% is an organometallic compound used as an auxiliary drier in the

formulation of alkyd-based paints, inks, and coatings. It promotes through-drying by accelerating the oxidative polymerization of unsaturated bonds in drying oils and resins. Manganese acts synergistically with cobalt and calcium driers to balance surface and

through-drying performance.

**Typical Properties** Physical form Liquid

ColorReddish BrownMetal content7.80 - 8.20 %Specific Gravity0.931 - 0.961Non-volatile matter45 - 55Viscosity15 - 25

Features and benefits Effective Curing: Enhances internal drying of alkyd films

Anti-Wrinkle: Prevents surface wrinkling with cobalt

**Color Stable**: Warm tone, minimal discoloration in light shades **Compatible**: Works well with cobalt, calcium, zirconium, lithium

Low Volatility: Stable under normal storage

**Applications** Recommended to be used in:

Alkyd paints (air-drying and baking systems)

Varnishes and enamels

Industrial metal and wood coatings

Printing inks

Decorative and protective coatings

Guidelines for use Recommended dosage: 0.02 - 0.10% manganese metal on total formulation weight.

Typically used alongside cobalt octoate (for surface drying) and calcium/zirconium driers (for pigm

wetting and dispersion).

Add during the final stage of production, under good agitation.

**Handling Instructions** Store in a cool, dry, and well-ventilated area.

Keep container tightly sealed when not in use.

Avoid skin and eye contact. Use protective gloves and eyewear. Keep away from sparks, open flames, and oxidizing materials...

**Shelf life** It is recommended that Goldstab Manganese Octoate should be used within 12 months from

the date of manufacture when stored in sealed original containers between 5°C and 30°C.

**Note:** The information and data provided herein in is good faith and are based on the current knowledge and experience of Goldstab Organics Pvt. Ltd. As there are many factors that may affect the processing and use of the product, we recommend users carry out investigations and tests to determine the suitability of the product for particular purpose prior to use.

Phone: +91-2267489899 Email: sales@goldstab.com Rev.no.: 01 Rev. date: September 2025