

Goldstab Zinc Octoate 18%

Description	Goldstab Zinc Octoate 18% is a metal carboxylate or metal salt of octanoic acid diluted with industrial solvents	
Typical Properties	Physical form	Clear Liquid
	Color	Pale yellow
	Non- volatile matter	75 ± 5%
	Metal content	18.0 ± 0.2%
	Viscosity	16 ± 2 seconds on B4 Ford's cup
	Specific Gravity	1.06 ± 0.03
Features and benefits	Goldstab Zinc Octoate 18% is an auxiliary drier. It keeps the film of the paint open by retarding the surface drying thus promotes the through drying and avoids surface wrinkling. Zinc addition maintains the colour and glass of the film.	
Applications	Recommended to be used in: Oxidative drier for polyester resin	
Guidelines for use	Dosage of 0.5 to 3.0 parts of Goldstab Zinc Octoate 18% per 100 parts of resin is recommended. Depending upon various factors such as active functional groups, glass transition temperature and other additives used in formulation the final formulation can be optimized. Extensive performance data of Goldstab Zinc Octoate 18% is available upon request.	
Handling Instructions	Goldstab Zinc Octoate 18% is a toxic product and proper care should be taken while handling. It is highly recommended to use nose mask and gloves and avoid unnecessary personal contact.	
Shelf life	It is recommended that Goldstab Zinc Octoate 18% should be used before 24 months from the date of manufacturing	

Note: The information and data provided herein in is good faith and are based on the current knowledge and experience of Goldstab Organics Pvt. Ltd. As there are many factors that may affect the processing and use of product, we recommend users to carry investigations and tests to determine suitability of the product for particular purpose prior to use.