

**Drocure™ 5130****D.R.COATS INK & RESINS PVT.LTD.**

Description: Drocure™ 5130 is a versatile Lewis based catalyst for curing of Epoxy Resins. It is a technical grade of tris-(dimethylaminomethyl) phenol.

Application:

- Activator for aminoamides, reactive polyamides and amine adducts.
- Can be used as catalyst with other curing agents for coatings, castings, floorings, concrete, adhesive, sealant and caulk.

Advantage:

- It is also used as catalyst for blend of liquid epoxy resin and liquid polysulfide for body solder, sealant and concrete adhesive applications.

Technical Specification:

Property	Unit	Test Method	Value
Appearance	---	Visual	Light Yellow Amber Liquid to Brownish Liquid
Color	CGS	ASTM D 1544	8 Max
Amine value	Mg KOH/gm	ASTM D 2074	580-640
Viscosity @ 25°C by BF	P	ASTM D 2196	1.5-3.5
Recommended Use Level	phr	---	1-5

Shelf Life: It is recommended that the material should be used within 12 months from the date of manufacture.

Packing: 200 ltr MS/HDPE Drums.

Storage: Store at dry and cool place between 18 to 23 °C in original sealed drums.

DISCLAIMER: The information contained in this sheet is accurate to the best of our knowledge .In View of conditions of use being totally beyond our control, customers should evaluate the data and make their own tests to determine the suitability of our product for their special use All our products are sold without warranty express or implied, and no liability can be accepted in respect of information and products.